


Caddy

Tank for heating water with innovative thermic chimney and incorporated sanitary exchanger

300÷800 L

Innovative tank for alternative source and instant sanitary water production. Caddy is the synthesis of integration tanks to its sanitary water exchanger for the best performance with different energetic sources.

- Insulation made of soft polyurethane 100 mm.
- Solar intergration for HDW and heating technical water.
- Gas boiler integration.
- Wood boiler integration.
- Instantaneous HDW
- Stratification with hydraulic chimney.
- 4 m² copper coil exchanger.
- Sanitary water exchanger to choose.
- Absolute hygiene.
- Long durability.



| Caddy | | 300 | 500 | 800 |
|----------------------------------|----------------|------|------|------|
| Total storage | l | 270 | 450 | 700 |
| Isolation thickness | mm | 100 | 100 | 100 |
| Total height insulation included | mm | 1625 | 1765 | 1780 |
| Diameter isolation included | mm | 700 | 850 | 990 |
| Lower collector pipe coil | m ² | 1,9 | 2,5 | 2,5 |
| Water capacity of pipe coil | l | 11,4 | 14,9 | 14,2 |
| Power input | kW | 45 | 60 | 63 |
| Unladen weight | kg | 130 | 150 | 220 |
| Heating max working pressure | bar | 3 | 3 | 3 |
| Boiler max working temp | °C | 95 | 95 | 95 |

Extractable heat-exchanger kit, complete with bored flange, upper cap for flange and nuts and bolts, already included

| | | 4 |
|-------------------------------|-------------------|-----|
| Heat exchanger surface | m ² | 4,0 |
| Pipe coil water capacity | l | 2,8 |
| Power input | kW | 80 |
| Domestic hot water production | m ³ /h | 2,0 |
| Pressure loss | mbar | 584 |
| Power code (DIN 4708) | NL | 20 |



* For the accessories see the Puffroller's page