


# Puffroller & PuffrollerOut

Optimal for the storage  
of chilled and hot water

60÷880 L

- To be integrated on all kind of plants.
- Storage rapidity, abundant and continuous erogation.
- High efficiency for low exercise costs
- Absolute hygiene
- Long durability without corrosion
- Simplicity of installation
- Inside untreated.
- Fixture point for wall installation for models 60/120 and 200 l.
- The models 60/120 and 200l can be installed in horizontal or vertical position.
- Polyurethane foam insulation 50 mm.
- Prepared for inserting auxiliary electric resistance.
- Coating suitable for outdoor installation (PuffrollerOut only)



Puffroller / PuffrollerOut		60	120	200	280	400	480	750	880	1400
Total storage	l	57	123	203	277	399	473	732	855	1420
Isolation thickness	mm	50	50	50	50	50	50	100	100	100
Total height insulation included	mm	935	1100	1395	1560	1540	1840	1725	1975	2090
Diameter isolation included	mm	380	510	550	600	700	700	850	850	1060
Diameter isolation included <b>PuffrollerOut</b>	mm	500	600	650	700	800	800	990	990	1200
Unloaded weight	kg	25	35	45	55	95	100	170	190	240
Heating max working pressure	bar	6	6	6	6	6	6	6	6	6
Boiler max working temp	°C	95	95	95	95	95	95	95	95	95
Hydraulic connections		60	120	200	280	400	480	750	880	1400
Air evacuation		1"	1"	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4
Boiler inlet		1" 1/4	1" 1/4	1" 1/2	2"	2" 1/2	2" 1/2	3"	3"	4"
Heating inlet		-	-	-	-	-	2" 1/2	3"	3"	4"
Boiler - heating outlet		1" 1/4	1" 1/4	1" 1/2	2"	2" 1/2	2" 1/2	3"	3"	4"
Thermometer		1/2	1/2	1/2	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Feeler		1/2	1/2	1/2	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Electric heater		1" 1/2	1" 1/2	1" 1/2	1" 1/2	1" 1/2	1" 1/2	1" 1/2	1" 1/2	2"
Drain		1/2	1/2	1/2	3/4"	3/4"	3/4"	1"	1"	1"

## Accessories

- RE1.5M3** Electrical resistance single phase 1,5 kW (L=340 mm) \*
- RE2.0M3** Electrical resistance single phase 2,0 kW (L=390 mm) \*
- RE3.0M3** Electrical resistance single phase 3,0 kW (L=390 mm) \*

- VAS**  
**VE24AT**  
**VEP35AT**

Anti-scalding valve  
Expansion vessel 24 l for tanks with capacity up to 500 l  
Expansion vessel 35 l for tanks with capacity up to 1000 l

\* Not for model 60-750-880-1400

## Versions

**Standard**

Only for indoor installation

**Out**

For indoor and outdoor installation